

ifications

Special Education School Bus Specifications

Quantity: 6

Dealer License # is

sales and service facilities

Excesses and deviations.

With your bid, please note all

items and deviations.

items that must have a red-

YES NO

Additional w/ Lift

General school bus requirements

Front

Newer model 2020 or newer

36-4 wheel Chairs with continuous track

Seats - See Attached Floor Plan

Gallatin, TN 37066

Owners manual

Owners product service training

Chassis components SCS

Warra

1.29 or greater or road s

1.7 CFM, minimum

1. No SS 1200 parts # 5400850-7010 or Bendix AD-9 w/ heater

3. 190 or greater cubic inch capacity, Bendix DV-2 with Heater

5 or Leece Neville

1.5 minimum with oil bath with c lube

ifications

21,000 minimum lbs. with

3-1950 Ford Series

Factory Installed in Battery Department

750 watt with bumper mounted receptacle

adjusters

dash

16.5" x 8" minimum

6.5" x 4" minimum

bracket

are inches

ft

no exceptions

Beow rear bumper on left side of frame with exhaust mitigator

row hooks

at the engine

at guard

30" gap between frame rails, fuel door with thumb latch

te at interior floor

Dual air gauges

Transmission temperature gauge, fast idle switch

se control

c Titanium Line

with sin e door

rate with GVWR

3000 lbs. rati

Tilt and teles ie steer

punted are

mounted

hood, transpond fluid & fuel sense

27 on trailer (list exact wheelbase)

22.5" diameter coated black

and chassis

mission warranties

driver, access without tools

101 w/ copy of complete list of A/C parts

31 specifications

1m (not in side panel)

polycarbonate

vented fans

vented glass

in with vandalo

ded into headlights

under and over driver window

100 w/ buzzers

Lo 9000 or Spheros equivalent

black floor covering in Koroseal pebble entrance steps

with metal aisle trim

metal housings

7 holes, minimum

Acousti-ne full length of bus

100 w/ removable filter

greater 30,000 BTU's min.

1 valve(s)

5" numbers-four sides

temp showing year model

10" side walls. R value = 5.7

filled under driver toeboard

Air Con:

Black floor covering in Koroseal pebble entrance steps

Acousti-ne

1
3
S
S
i

rt
Ta
Tape
ors

artment

ce
rivers
river
river

se

Seats and Belts

Seat U

Seacurement

nels
id
p
m

r Track

Blue fire blo kick anel-ri ht side stora e ch-left side

Air ride distal cover 2 sho fabric insert

Lap/shoulder belt (orange) with warning indicator, adjustable back

Seats 6 - 39" Tract MTD and 9 - 30" 6 Tract MTD

uard Seats W/ 3 Point Seat Belts (FE200868-4) and Child Restraint

Blue

Sure-Lok retractable T FE200855S (4 Sets) w/ sto ouches FF612-4C

Interior - Aluminized steel side walls

Disconnect all body circuits, 100 amp minimum

Roof mounted Specialty 515-400 with guard or equal

Trans 2000 Electric erated

Wheelchair Tract 4 rows continuous in floor & 1 Continuous Track over windows

Continuous Four (4) Track System

Recessed in Plywood

For fresh air & static roof vent

Windows with 12" openings, tinted glass

Sliding, aluminum sash, tempered

Color tinted, bonded in place

Seals beside windshield and cowl steps

Attention feature on turn signal lever

Color & number coded

Electrical access without using multiplex wiring

112 db required

To meet State specs

Appropriate switch to be provided

Part numbers # 's supplied to successful bidder

Good intake plenum, and headlight bezels

Attachment - Rep. Frank Bowden for proper installation



Additional fenders around rear wheel

See II and all accessories Contact @ 615-889-4756 for installation and price

All units to have common key

Mounted with cut off switch in box

LIFT



BARRIERS



STD/DOT SEATS



CHILD RESTRAINT SEATS



NEW STUDENT S

CEW STUDENT SAFETY CR

36

36 45

WHEELCHAIR

HATCH

ROOF EXIT

TRACK

TRACK *
*

STROBE



4112-HVR

12 chan rec-8 analog 4 IP cam

41-PANIC-KIT

Panic Button Kit for 41's

41-PANIC-CABLE

Cable for 41-Panic Use with all but the 4000HVB

41-UPS

3ft usb a to b

UPS back-up battery for the 4000-HVR, 4100-HVR & 4112-HVF

SV-DECAL

Audio & Video Recording in Progress

SV-EXT16-1080S

AHD curb side 16MM camera for 4100 & 4112 HVR

SV-EXT8-1080C

AHD curb side 8MM camera for 4100 & 4112 HVR

AHD-2 8M-WT

2 8mm camera for 4000

AHD-WV

AHD Wide View Camera

SVS-5MMF

5m M/F THREADED CABLE

41-WS-BRKT

front windshield bracket

SVS-15MMF

15m M/F THREADED CABLE

SVS-10MMF

10m M/F THREADED CABLE

RICON TITANIUM LINE

K-SER ES® L FT: Models: K2005-K5510

Rated Load Capacity

Lift Weight

Approx. 400-425 lbs. / 181 - 193 kg

Hydraulic Cylinders: 1.5" Power-Up / Gravity Down
Motor Rating @ 12V DC: 65 amp avg. / cycle 1750 psi

Hand Pump
Dura-Touch and EZ-Roll are trademarks of Ricon Corporation. All Rights Reserved Ricon Corp.

Use the right to disassemble, repair or modify the product.

Dimensions Inches/Millimeters

Height
(folded)

48/1219